

Automatenstahl-Rund blank gezogen

Seite 1

EN 10 277 (DIN 1651)

a 3 m HL

l = Standardabmessungen

mm Ø	kg/m	EN 11SMn30+C (DIN 9SMn28k)	EN 11SMnPb30+C (DIN 9SMnPb28k)
2	0,025		
3	0,056		
4	0,099		
5	0,154		
6	0,222		
7	0,302		
8	0,395		
9	0,499		
10	0,617		
11	0,746		
12	0,888		
13	1,042		
14	1,208		
15	1,387		
16	1,58		
17	1,78		
18	2,00		
19	2,23		
20	2,47		
21	2,72		
22	2,98		
23	3,26		
24	3,55		
25	3,85		
26	4,17		
27	4,50		
28	4,83		
29	5,19		
30	5,55		
32	6,31		
33	6,71		
34	7,13		
35	7,55		
36	7,99		

Automatenstahl-Rund blank gezogen
EN 10 277 (DIN 1651)
a 3 m HL

Seite 2

l = Standardabmessungen

mm Ø	kg/m	EN 11SMn30+C (DIN 9SMn28k)	EN 11SMnPb30+C (DIN 9SMnPb28k)
38	8,90		
40	9,87		
41	10,4		
42	10,9		
45	12,5		
46	13,0		
48	14,2		
50	15,4		
52	16,7		
55	18,7		
56	19,3		
58	20,7		
60	22,2		
62	23,7		
65	26,0		
70	30,2		
75	34,7		
80	39,5		
85	44,5		
90	49,9		
95	55,6		
100	61,7		
105	68,0		
110	74,6		
115	81,5		
120	88,8		
125	96,3		
130	104,2		
140	120,8		
150	138,5		
160	157,8		
180	200,0		
200	247,0		

Nicht aufgeführte Güten und Abmessungen auf Anfrage.