

Edelstahl Quadratrohre geschweißt
Güte 1.4301* EN 10 088 (DIN 17 440)
a 6 m HL

Abmessung	1	1,2	1,5	2	2,5	3	4	5	6	8	10
	kg/m										
10 x 10 x	0,300										
15 x 15 x	0,463	0,550	0,676								
16 x 16 x	0,496		0,725								
20 x 20 x	0,626	0,745	0,920	1,202	1,409						
25 x 25 x	0,789	0,941	1,164	1,527	1,878						
30 x 30 x		1,136	1,409	1,853	2,285	2,704					
35 x 35 x			1,653	2,178		3,193					
40 x 40 x		1,526	1,897	2,504	3,099	3,681	4,808				
45 x 45 x				2,830							
50 x 50 x			2,385	3,155	3,913	4,657	6,110	7,512			
60 x 60 x			2,873	3,806	4,726	5,634	7,412	9,140			
70 x 70 x				4,457		6,611	8,714	10,767			
80 x 80 x				5,108		7,587	10,016	12,395	14,724		
100 x 100 x				6,410		9,540	12,620	15,650	18,630		
120 x 120 x						11,493	15,224	18,905	22,536	29,647	
150 x 150 x						14,423	19,131	23,788	28,359	37,460	46,324
200 x 200 x						19,306	25,641	31,962	38,161	50,481	

* Alternativ auch in Güte 1.4571 / 1.4404

Unser Service:

- Geschliffen K240 / K320
- Fixlang gesägt